

IN THE CLAIMS

1. (Previously Presented) A system to remotely configure a radio, comprising:

a graphical interface on a first network device that displays an association page from which a user graphically establishes an association list between a first set of configuration data and a second set of displayed configuration data in a user profile in a remote database;

a radio having a digital controller that is able to communicate with the remote database to retrieve and apply the user profile to facilitate operation of the radio; and

a location identifier representative of a geographic location of the radio for identifying the second set of configuration data.

2. (Previously Presented) The system of claim 1, wherein a plurality of preset button identifiers is the first set of configuration data; and

a plurality of radio stations is the second set of configuration data.

3. (Original) The system of claim 2, further comprising:

a preset button in a plurality of buttons located at the radio being associated with a radio station in response to receipt of the association list at the radio.

4. (Cancelled)

5. (Original) The system of claim 1, further comprising:

an alarm configuration page displayed in the graphical interface that establishes an alarm time list with an associated alarm type in the user profile.
6. (Cancelled)
7. (Previously Presented) The system of claim 5, wherein an alarm clock in the radio is set in response to receipt of the alarm list and the associated alarm type from the user profile.
8. (Previously Presented) The system of claim 5, wherein receipt of a time synchronization message at the radio results in an alarm clock being set.
9. (Original) The system of claim 1, wherein the graphical interface is a web browser.
10. (Previously Presented) A method for remotely configuring a radio, comprising:

displaying on a graphical interface on a first network device an association page from which a user graphically establishes an association list between a first set of configuration data and a second set of displayed configuration data in a user profile in a remote database;

determining a location identifier representative of a location of the radio;

identifying the second set of configuration data based on the location identifier;

and

retrieving the user profile by a digital controller in the radio that is able to communicate with the remote database to facilitate the operation of the radio.

11. (Previously Presented) The method of claim 10, further comprising:
sending the location identifier to the remote database; and
receiving at least the second set of configuration data at the first network device

12. (Previously Presented) The method of claim 10, further comprising:
generating a time synchronization message at a computing device;
sending the time synchronization message to the radio; and
setting a clock in the radio in response to reception of the time synchronization message.

13. (Original) The method of claim 10, further comprising:
displaying an alarm configuration page in the graphical user interface;
creating an alarm association between an alarm action and a time of day;
storing the alarm association in the user profile located in the remote database;
and;
communicating the alarm association to the radio.

14. (Previously Presented) The method of claim 10, wherein establishing further includes:

assigning a first preset button identifier from a plurality of preset buttons that comprise the first set of configuration data to a radio station from a plurality of radio stations that comprise the second set of configuration data.

15. (Original) The method of claim 14, wherein communicating further includes: configuring a first preset button in a plurality of preset buttons in the radio to select the radio station upon the selection of the first preset radio button.

Claims 16-18 (Cancelled)

19. (Previously Presented) A system for remotely configuring a radio, comprising:
means for displaying on a graphical interface on a first network device an association page from which a user graphically establishes an association list between a first set of configuration data and a second set of displayed configuration data in a user profile in a remote database;

means for determining a location identifier representative of a location of the radio;

means for determining the second set of configuration data based on the location identifier; and

means for retrieving the user profile by a digital controller in the radio that is able to communicate with the remote database to facilitate the operation of the radio .

20. (Previously Presented) The system of Claim 19, further comprising:

means for sending the location identifier to the remote database; and
means for receiving at least the second set of configuration data at the first network device.

21. (Previously Presented) The system of claim 19, further comprising:
means for generating a time synchronization message at a computing device;
means for sending the time synchronization message to the radio; and
means for setting a clock in the radio in response to reception of the time synchronization message.

22. (Original) The system of claim 19, further comprising:
means for displaying an alarm configuration page in the graphical user interface;
means for creating an alarm association between an alarm action and a time of day;
means for storing the alarm association in the user profile located in the remote database; and
means for communicating the alarm association to the radio.

23. (Previously Presented) The system of claim 19, further including:
means for assigning a first preset button identifier from plurality of preset buttons that comprise the first set of configuration data to a radio station from a plurality of radio stations that comprise the second set of configuration data.

24. (Previously Presented) The system of claim 23, further including:

means for configuring a first preset button in a plurality of preset buttons in the radio to select the radio station upon the selection of the first preset radio button.
25. (Previously Presented) The system of Claim 10 wherein the step of determining a location identifier includes entering the location identifier at the graphical interface.
26. (Previously Presented) The system of Claim 19 where in the means for determining a location identifier include means for entering the location identifier at the graphical interface.